

M-SERIES



GunDigest

2015 RIFLESCOPE
OF THE YEAR

**BUILT IN
GERMANY.
DESIGNED FOR
THE WORLD.**

THE GERMAN-
MADE M-SERIES
FEATURES WORLD-
CLASS ENGINEERING
AND OPTICAL
SYSTEMS, BUILT TO
STRICT MILITARY
SPECIFICATIONS AND
PRECISELY CRAFTED
FOR VICTORY - ON THE
BATTLEFIELD, OR IN
COMPETITION.

M-SERIES OVERALL FEATURES

- MIL-SPEC
- 5X / 6X ZOOM RANGE
- BROADBAND ANTI-REFLECTION COATINGS
- OPTIMIZED EXTERIOR DESIGN
- PRECISE WINDAGE/ELEVATION ADJUSTMENT
- ILLUMINATED RETICLE
- FOGPROOF & WATERPROOF DOWN TO 33 FT.
- SHOCKPROOF



The premier Steiner long-range scope with 34 mm tube, true 25x magnification, etched glass reticle, and DuoScale™ elevation with second-rotation scale that's hidden when inactive.



M5Xi 5-25X56

TUBE DIAMETER 34 MM | LENGTH 16.6 IN. | BATTERY CR2450
ITEM NO. 5525 (G2B MIL-DOT) | UPC 000381855251
ITEM NO. 5550 (MSR) | UPC 000381855503
ITEM NO. 8704 (HORUS® H59®) | UPC 840229101580
ITEM NO. 8704-T3 (HORUS TREMOR® 3) | UPC 840229101962

Medium-range scope with 34 mm tube, etched glass reticle, and patented DuoScale™ elevation adjustment with a second-rotation scale that's hidden when inactive.



M5Xi 3-15X50

TUBE DIAMETER 34 MM | LENGTH 14.2 IN. | BATTERY CR2450
ITEM NO. 5572 (G2B MIL-DOT) | UPC 000381855725
ITEM NO. 5573 (MSR) | UPC 000381855732
ITEM NO. 8707-H59 (HORUS® H59®) | UPC 840229101887
ITEM NO. 8707-T2 (HORUS TREMOR® 2) | UPC 840229101894
ITEM NO. 8707-T3 (HORUS TREMOR® 3) | UPC 840229101900

Close-combat scope with 30 mm tube, Rapid Dot Reticle calibrated in 5.56 or 7.62, true 1x eyes-open capability for situational awareness, and 5x power to engage distant targets.



M5Xi 1-5X24


TUBE DIAMETER 30 MM | LENGTH 11.6 IN. | BATTERY CR2450
ITEM NO. 5571 (RAPID DOT 5.56) | UPC 000381855718
ITEM NO. 5570 (RAPID DOT 7.62) | UPC 000381855701

One of the most versatile in the series, the new 1-6x scope will match perfectly with any tactical or competition rifle, or dangerous game hunting rifle. Available with the Rapid Dot reticle in 5.56 or 7.62.




M6Xi 1-6X24


TUBE DIAMETER 30 MM | LENGTH 11.25 IN. | BATTERY CR2450
ITEM NO. 8708-556 (RAPID DOT 5.56 CCW USA) | UPC 840229101009
ITEM NO. 8708-762 (RAPID DOT 7.62 CCW USA) | UPC 840229101009




MSR Reticle




Horus® H59®
Reticle



HORUS Tremor® 3
Reticle



Rapid Dot Reticle



G2B Mil-Dot Reticle

SPECIFICATIONS

	M5Xi				M6Xi			
	1-5x24	1-5x24	3-15x50	3-15x50	5-25x56	5-25x56	5-25x56	1-6x24
ITEM NUMBER	5570	5571	8707-H59 / 8707-T3	5572 / 5573	5525	5550	8704 / 8704-T3	8708-556 / 8708-762
MAGNIFICATION	1-5x	1-5x	3-15x	3-15x	5-25x	5-25x	5-25x	1-6x
OBJECTIVE LENS DIA.(MM)	24	24	50	50	56	56	56	24
TUBE DIAMETER	30mm	30mm	34mm	34mm	34mm	34mm	34mm	30mm
FOCAL PLANE	2nd	2nd	1st	1st	1st	1st	1st	2nd
FIELD OF VIEW AT 100 YD. (FT.) LOW/HIGH	118.1 - 23.7	118.1 - 23.7	39.7 - 7.9	39.7 - 7.9	23.6 - 4.6	23.6 - 4.6	23.6 - 4.6	118.1-23.7
EYE RELIEF (IN.) LOW/HIGH	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3	3.5 - 4.3
EXIT PUPIL (MM) LOW/HIGH	11.5 - 7.2	11.5 - 7.2	10.4 - 3.3	10.4 - 3.3	9.8 - 2.2	9.8 - 2.2	9.8 - 2.2	11.5 - 7.2
LENGTH (IN.)	11.6	11.6	14.2	14.2	16.6	16.6	16.6	11.25
WEIGHT (OZ.)	21.2	21.2	32.5	32.5	36.3	36.3	36.3	22
DIOPTER ADJUSTMENT RANGE	+2 to -3	+2 to -3	+2 to -3	+2 to -3	+2 to -3	+2 to -3	+2 to -3	+2 to -3
RETICLE	Rapid Dot 7.62	Rapid Dot 5.56	Horus® H59® / Horus Tremor® 2 / Horus Tremor® 3	G2B Mil-Dot /MSR	G2B Mil-Dot	MSR	Horus® H59® / Horus Tremor® 3	Rapid Dot 5.56 / Rapid Dot 7.62
ILLUMINATION CONTROL	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops	Rotary Digital Control with Intermediate Stops
ELEVATION ADJUSTMENT KNOB	Resettable Zero	Resettable Zero	Duo Scale™ / Resettable Zero	Duo Scale™ / Resettable Zero	Duo Scale™ / Resettable Zero	Duo Scale™ / Resettable Zero	Duo Scale™ / Resettable Zero	Resettable Zero
WINDAGE/ELEVATION CLICK VALUE	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)	1 cm (0.1 mrad)
WINDAGE RANGE @ 100 M	160 cm (16 mils)	160 cm (16 mils)	± 60 cm (± 6 mils)	± 60 cm (± 6 mils)	± 60 cm (± 6 mils)	± 60 cm (± 6 mils)	± 60 cm (± 6 mils)	160 cm (16 mils)
ELEVATION RANGE @ 100 M	320 cm (32 mils)	320 cm (32 mils)	260 cm (26 mils)	260 cm (26 mils)	260 cm (26 mils)	260 cm (26 mils)	260 cm (26 mils)	320 cm (32 mils)
PARALLAX/FOCUS	Fixed	Fixed	Side Focus	Side Focus	Side Focus	Side Focus	Side Focus	Fixed
PARALLAX/ FOCUS RANGE	328 ft.	328 ft.	164 ft. to Infinity	164 ft. to Infinity	164 ft. to Infinity	164 ft. to Infinity	164 ft. to Infinity	328 ft.
NITROGEN FILLED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OPERATING TEMP. RANGE	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F
LENS CAPS	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
WATERPROOF/ FOGPROOF	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.
BATTERY	CR2450	CR2450	CR2450	CR2450	CR2450	CR2450	CR2450	CR2450
SPECIAL FEATURES	Resettable Turrets, Zero Stop	Resettable Turrets, Zero Stop	Resettable Turrets, Second Rotation Indicator, Zero Stop	Resettable Turrets, Second Rotation Indicator, Zero Stop	Resettable Turrets, Second Rotation Indicator, Zero Stop	Resettable Turrets, Second Rotation Indicator, Zero Stop	Resettable Turrets, Second Rotation Indicator, Zero Stop	Resettable Turrets, Zero Stop
WARRANTY	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty
MSRP PRICE	\$2,989.99	\$2,989.99	\$3,794.99	\$3,330.99 / \$3,445.99	\$3,620.99	\$3,737.99	\$4,312.99	