

Mk4



Technical Manual

Mk4 BATTLE LIGHT

WEAPON MOUNTED WHITE LIGHT LED 500 LUMENS

STEINER 
Nothing Escapes You

MAINTENANCE:

- Never use strong cleaners or solvents on housing.
- Use soft towel and soapy water to clean external housing.
- Use damp towel to clean internal battery compartment. Excess moisture inside battery compartment may damage unit.
- Use alcohol and soft towel to clean front window.

OPTIONAL ACCESSORIES (not included)

- Mk4 Dual Tailcap (Push Button/Remote Cable) - Black (Item # 9161)
- Mk4 Low Profile Offset Mount - Black (Item # 9165)
- 7" Y-Remote cable pressure pad switch. Connects Mk4 Battle Light and OTAL-A, OTAL-Classic, CQBL-1, DBAL-A2, DBAL-D2, DBAL-I2 (Item # 9145)

STEINER HERITAGE™ WARRANTY

For any reason other than theft or deliberate misuse, we will repair or replace your Steiner battle light at no charge to you should it become damaged or defective - no questions asked.

- No warranty card needed
- No receipt required
- Fully transferable - from generation to generation

The Mk4 Weapon-Mounted Tactical Light features a stunning 500 lumen LED in a sleek, compact package. The Mk4 mounts to any MIL-STD-1913/Picatinny rail using our low profile thumb screw mount that neatly tucks the light in between the top and side rails of an M4/M16.

BATTERY INSTALLATION:

1. Install batteries prior to mounting on to weapon.
2. Rotate flashlight head counter clock wise and remove from battery housing.
3. Install batteries in correct orientation as marked on housing.
4. Install flashlight head by turning clock wise onto battery tube.
5. Do not use any tools to turn flashlight head.



MOUNTING TO WEAPON:

1. Ensure weapon is unloaded and magazine is removed prior to mounting unit.
2. Open thumb screw by rotating counter clock wise. Ensure grabber rail is opened.
3. Install unit on to weapon in desired location.
4. Rotate thumb screw clock wise to secure mount on to rail. Ensure unit is firmly attached to weapon prior to shooting.



SPECIFICATIONS:

- Includes thumb screw mount and pressure pad
- Push-button or remote cable pressure pad activation
- Momentary / Constant On
- Mount: MIL-STD-1913/Picatinny rail
- Type: White Light LED
- Lamp: Light Emitting Diode
- Lumens: 500
- Divergence: 10°
- Range: 300 m
- Weight: 4.9 oz. / 138.91 grams
- Length: 5.98 in. / 15.19 cm
- Diameter: 1.0 in. / 2.54 cm
- Battery: 2 x CR 123A or 1 x 18650 rechargeable
- Battery Life: 1.25 hours or 1.75 hours
- Material: Anodized Aircraft Aluminum 6061-T6,
MIL-SPEC Type III Hardcoat Anodized
- Environment: Waterproof to 5 m
- Warranty: Heritage Warranty™



STEINER-OPTIK

331 East 8th Street • Greeley, CO 80631

Tel: (888) 228-7747 • Fax: (970) 356-8702

Customer Service: laserlightsinfo@steiner-optics.com
steiner-optics.com